


PROTRON ECLYPSE



The PROTRON ECLYPSE™ is a versatile high powered 1000W air cooled IPX4 outdoor rated color blinder, strobe, wash luminaire. Features include (96) 10W CREE RGBW 4-in-1 LEDs, 31° beam / 63° field angles, 27,000+ total lumen output, brilliant eye candy effects, selectable pixel mapping zones, strobe intensity, duration, rate, and FX control, super high speed (1-25fps) adjustable strobe, DMX, RDM, Kling-NET, and Art-NET protocol support, 8/16 bit RGB and RGBW smooth color mixing modes, adjustable/removable yoke bracket with 3-position holes, interlocking system for multiple unit matrix designs, IP54 3/5pin DMX, RJ45 etherCON, Seetronic IP65 power in/out connections, 4-button control pane with OLED menu display, and a multi-voltage universal auto switching power supply (100-240v).

FEATURES

- Versatile Color Blinder, Strobe, Wash Luminaire**
- High Powered 1000W Air Cooled IPX4 Outdoor Rated**
- 96 10W CREE RGBW 4-in-1 LEDs**
- 31° Beam / 58° Field Angles**
- 27,000+ Total Lumen Output**
- Brilliant Eye Candy Effects**
- Selectable Pixel Mapping Control Zones**
- Strobe Intensity, Duration, Rate, and FX Control**
- Super High Speed (1-25fps) Adjustable Strobe**
- DMX, RDM, Kling-NET and Art-NET Protocol Support**
- 8/16 Bit RGB and RGBW Smooth Color Mixing Modes**
- Adjustable/Removable Yoke Bracket w/3-Position Holes**
- Interlocking System for Multiple Unit Matrix Designs**



IPX4 Outdoor Rated

Specifications are subject to change without notice ©Elation Professional 01/24/19

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

SPECIFICATIONS

SOURCE

96 10W CREE RGBW 4-in-1 LEDs
 15,000 Hour Average LED Life*

*May vary depending on several factors including but not limited to:
 Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control and Dimming.

PHOTOMETRIC DATA

31° Beam / 63° Field Angles
 27,000+ Total Lumen Output

EFFECTS

Color Blinder, Strobe, and Wash
 Brilliant Eye Candy Effects
 Selectable Pixel Mapping Control Zones
 Strobe Intensity, Duration, Rate, and FX Control
 Super High Speed (1-25fps) Adjustable Strobe
 8/16 Bit RGB and RGBW Smooth Color Mixing Modes

COLOR

RGBW

CONTROL / CONNECTIONS

Multiple DMX Channel Modes (24 total channels)
 4 Button Touch Control Panel with OLED Menu Display
 DMX, RDM, Kling-NET, and Art-NET Protocol Support
 IP65 3/5pin DMX and RJ45 etherCON In/Out
 IP65 Seetronic Power In/Out
 Fixture-to-Fixture Interlocking Alignment Pins/Locks

SIZE / WEIGHT

Length: 24.9" (633mm)
 Width: 7.0" (177.5mm)
 Vertical Height: 14.4" (364.8mm)
 Weight: 34.6 lbs. (15.7kg)


ELECTRICAL / THERMAL

AC 100-240V - 50/60Hz
 843W Max Power Consumption
 14°F to 113°F (-10°C to 45°C)

APPROVALS / RATINGS



PIXEL MAPPING CONTROL ZONES



ORDERING INFORMATION

PRO951	PROTRON ECLYPSE
TRIGGER CLAMP	Heavy Duty Wrap Around Hook Style Clamp
SCABLE60	Safety Cable 24" (610mm) 60 lbs. (27kg) Rating
STR527	5 ft. (1.5m) IP65 Seetronic 5pin PRO DMX Cable
NEU088	3 ft. (1m) powerCON TRUE1 Power Link Cable
CAT6PRO5	5 ft. (1.5m) CAT6 EtherCON Cable
	Additional cable lengths available

Specifications are subject to change without notice ©Elation Professional 01/24/19



Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
 323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
 +31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu